Well

All dimensions may not exceed perpendicular tolerance of ±2 cm



OH = Overhead
CW = Car width
CD = Car depth
CH = Car height
DW = Door widh
DH = Door height
FD = Floor distance
COP= Car Operating Panel
LOP= Landing Operating Panel



Speed: 0,6 m/s PIT: 120 cm OH: 320 cm	
CW: 100 cm CD: 125 cm CH: 210 cm	DW: 80 cm DH: 200 cm
FDmin.: 250 (CH+50 cm)	

HYDRAULIC MOTOR-ROOMLESS OPTIONS:

The space saving design cleverly houses the motor in a cabinet that can either be located on or recessed into an adjacent wall.

If space is limited beside the shaft the cabinet can be located up to 10 meters away.

HYDRAULIC MASCHINE ROOM REQUIREMENTS:

Maschine room min. dimension:
150 x 165

TYPICAL POWER REQUIREMENTS		
Motor Power (k.W.)	10	kW
Running current	21	A
Starting current	28	A
Overload current	36,4	A

Dimensions in cm.

Type: INDIRECT 480 kg TL8-TL8		Drawn By: Tomi Irgolič Date: 30.01.2007	SEC
HYDRAULIC	A4 1:25	Revision: 00	Page: 35